



Guide



Signal



Urban space



Roads



Private sites

ROAD MARKING PRODUCTS EXTRUDED HOT-COATED MATERIAL

NESSIE



EQUIPEMENTS DE LA ROUTE



NF 331

Hot-coated material for urban and road markings with a very high level of grip, ensuring maximum safety for users, including two-wheelers.

PERFORMANCE

NON-REFLECTIVE ROAD MARKING

P6 - Q3 - S4

REFLECTIVE MARKING

P5 - Q4 - R4 - S3

P: Traffic resistance
Q: Daytime visibility
R: Night-time visibility
S: Anti-slip

ADVANTAGES

USE

- Road users safety ensured with exceptional, long-lasting **grip** performance in town and on roads
- Excellent **night visibility** that remains constant over time: average retroreflection value > 320 (minimum required 150)
- Very good **daytime visibility**: average luminance ≥ 168 (minimum required 100), guaranteeing very white markings
- Products certified pursuant to standards NF EN 1436 and NF EN 1824

USE

- Flexibility and time savings in worksite management thanks to **multi-certification**
- Less disruption during works thanks to immediate restoration of traffic
- Zero packaging waste thanks to the hot-melt bag

SOCIAL AND ENVIRONMENTAL BENEFITS

- **WASTE REDUCTION**
Zero waste thanks to the hot-melt bag
- **BIO-BASED COMPONENTS**
100% plant-based resin
- **MADE IN FRANCE**
Made in the Île-de-France region



MADE IN
FRANCE



TECHNICAL CHARACTERISTICS

- Natural resin-based thermoplastic coating
- Density: 2.02kg/l
- Packaging: 20kg net hot-melt bags on 1,200kg shrink-wrapped pallets

Other packaging: please contact us



IMPLEMENTATION

- Melter-mixer and thermo machine equipped with an extrusion shoe
- New or old hydrocarbon surfaces
- Apply to a clean, dry surface
- On old road markings, apply a primer (contact us)
- Application temperature: 170 to 190°C
- Surface temperature limits: 5°C<T<40°C
- Maximum humidity: 80%



CONSUMPTION*	Non-reflective	Reflective
Product rate	2460g/m ²	1175g/m ²
Powdering rate	-	1,645g/m ²
Drying time	1min	

* According to certification conditions



SAFETY - STORAGE

- Product for professional use
- Storage: in a dry, ventilated place, away from frost, sunlight and any source of heat
- Shelf life: 24 months from date of manufacture, in unopened original packaging
- See the Safety Data Sheet at www.quickfds.fr