

OUESSANT CITY-ROAD



PERFORMANCE

NON-REFLECTIVE ROAD MARKING

P6 - Q3 - S3

REFLECTIVE ROAD MARKING

P3 - Q2 - R3 - S1

P: Traffic resistance

- Q: Daytime visibility
- R: Night-time visibility S: Anti-slip

SOCIAL AND ENVIRONMENTAL BENEFITS

- CIRCULAR ECONOMY 75% recyclable packaging
- WASTE REDUCTION Sakapo[®] reduces the weight of hazardous waste by 65
- MADE IN FRANCE Made in the Hauts-de-France region

Multi-purpose paint with excellent traffic resistance and strong adhesion in urban environments.

ADVANTAGES

VSE

- Excellent value for money
- Long life road marking: NF-certified product for 2 million wheelovers in urban traffic
- $\bullet~$ Very good anti-slip performance in urban use: SRT ≥ 0.58
- Products certified pursuant to standards NF EN 1436 and NF EN 1824

USE

- Flexibility and time savings in worksite management thanks to multi-certification
- Protect users' health: paint classified as non-harmful, guaranteed free of toluene and toxic pigments
- Sakapo[®] specific packaging facilitates waste management and reduces costs





OUESSANT CITY-ROAD



TECHNICAL CHARACTERISTICS

- Solvent-based acrylic paint
- Density: 1.49kg/l
- Packaging:
 - 25kg net metal buckets fitted with Sakapo[®]

Other packaging: please contact us



IMPLEMENTATION

- Pneumatic or airless machine (60 mesh filter)
- New or old hydrocarbon surfaces
- Apply to a clean, dry surface
- Surface temperature limits: 5°C<T<45°C
- Maximum humidity: 80%

CONSUMPTION*	Non-reflective	Reflective
Product rate	585g/m ²	580g/m ²
Powdering rate	135g/m²	440g/m ²
Drying time	19min	20min

* According to certification conditions



- Flammable product for professional use
- Storage: in a dry, ventilated place, away from frost, sunlight and any source of heat
- Shelf life: 12 months from date of manufacture, in unopened original packaging
- Soiled packaging and cleaning and rinsing products are waste to be treated in accordance with current regulations
- See the Safety Data Sheet at www.quickfds.fr

