



Alert



Signal/Inform



Protect



Motorways & Expressways



Roads

ON-BOARD ILLUMINATED SIGNS & EMERGENCY ARROW BOARD

# XERIUS



Emergency illuminated sign system equipped with a Variable Message Sign to signal and inform during works or work operations on dual carriageways.



LYNX remote control unit

## ADVANTAGES

### USE

- Complete, attractive and ergonomic equipment
- Effective user information tailored to every situation
- Messages are easy to read: high-performance LED displays
- Modular day/night lighting intensity
- Compatibility with a wide range of Emergency Arrow Boards (EAB) and multi-signals

### INSTALLATION & USE

- Can be fitted to all types of roadworks vehicles, from small utility vehicles to large vans
- Various remote control units with touchscreen and/or keypad for easy use
- Enhanced security with the night vision dual camera option

## SOCIAL AND ENVIRONMENTAL BENEFIT

- MADE IN FRANCE  
Made in the Nouvelle-Aquitaine region





## TECHNICAL CHARACTERISTICS

### > FRAME & HOUSING

- Aluminium frame protected by thermoformed ABS-PMMA aerodynamic housing

### > VARIABLE MESSAGE SIGN

- Up to 12 characters, composition height 200mm
- Up to 11 characters, composition height 250mm
- Brightness automatically adjusted by day/night unit (256 levels possible)



Night vision camera



Blue LED flashing light

### > OPTICAL ELEMENTS

- Emergency Arrow Boards
- Single-sided triangle, 1,250mm, class 2 film, fitted with
- 3 x 210mm diameter optics
- 2 orange LED rotating beacons
- Lifting by electric jack

### > AK FULL MATRIX LED TRIANGLE

- Single-sided 1,250mm black
- Definition of red and amber two-tone triangles

### > LYNX REMOTE CONTROL UNIT

- LCD screen (touch-sensitive) and backlit keypad
- Video inputs in NTSC format with RCA connector
- Compatible with the range and updated via USB port

### > SERVAL REMOTE CONTROL UNIT

- 12-key unit with backlit display



## OPTIONS

- Dual night vision camera
- Blue flashing light
- Second LED face on triangle 1250mm
- Additional work lights
- Pre-marking ramp, integrated operation in the centralised control unit



## COMPLIANCE

- For the VMS boards and characters: NF EN 12966, XP P98573
- For the KR43 arrow: class L8H/L8L of NF EN 12352